





Item #	Width (A)	Projection (B)	Height (C)
BLE-F-CGG	4 ¾"	9 ¼"	4 ¼"
BLE-F-WGG	4 ¾"	9 ¼"	4 ¼"
BLE-F-TGG	4 ¾"	9 ¼"	4 ¼"

Flush Mount Collection: Bullet Cast Guard


BLE-F-CGG



WGG – WIRE CAST GUARD



CGG-STANDARD CAST GUARD



TGG- HEAVY DUTY CAST GUARD

Item #	Standard Finishes	Glass Options	Wattage/Lamp Option	Correlated Color Temperature	Voltage
BLE-F-CGG	<i>Powder Coat:</i> 100 -Black 200 - White 300 -Dark Green 600 -Bronze 605 -Rust <i>Other:</i> 975 -Galvanized For additional colors, see color chart	<i>Vapor Proof Glass¹:</i> CLR - Clear FST - Frosted RIB - Ribbed For additional glass, see website	Incandescent (Max 100 watt per socket)		Standard 120V
BLE-F-WGG			GU-24 Bi-pin (Max 18 watt per socket)		
BLE-F-TGG			LED: 16.8 watt 1600 Lumen	2700K 3500K 4000K	Standard 120V
BLE-F-CGG	600	FST	LED <small>SAMPLE ORDER</small>	2700K	

ORDER SPECIFICS

BLE-F			
-------	--	--	--

Notes:

¹ Clear glass not recommended for LED option.

Suitable for Wet Location