Item #	Height (A)	Width (B)
CGG	10 ¼"	4 ¼"
TGG	10 ¼"	4 ¼"

Atomic Topless

CGG



CGG –STANDARD CAST GUARD

TGG – HEAVY DUTY CAST GUARD

Model #	Item #	Standard Finishes	Mounting Options	Mounting Color	Glass Options	Wattage/Lamp Option	Correlated Color Temperature	Voltage
S - Stem Mount **C -** Cord Hung **G-**Goose Neck **F-**Flush Mount	**CGG** **TGG**	*Other:* **975-**Galvanized *Powder Coat:* **100-**Black **200-** White **300-**Dark Green **600-**Bronze **605-**Rust ***For additional colors, see color chart***	*Cord:* Standard [1]: **SBK** Black **SWH** White Cotton [2]: **CRZ** Red Chevron [2]: **CGM** Grey **CBK** Black Cotton Twists [2]: **TBR** Brown **TBK** Black **TPT** Putty *Stem*: **ST** _____ ^Specify stem model *Gooseneck:* **G** _____ ^Specify gooseneck mode *Flush Mount:* **FM** *For additional mounting options and details, see mounting spec sheet*	*Cord:* Canopy color: Standard is: Same as fixture (leave code blank) OR **100-**Black **200-**White *Stem and Gooseneck*: Other: **975-**Galvanized **980-**Brushed Aluminum Powder Coat: **100-**Black **200-**White **300-**Dark Green **600-**Bronze **605-**Rust	*Vapor Proof Glass[1]:* **CLR-** Clear **FST-** Frosted **RIB-** Ribbed ***For additional glass, see website.***	Incandescent (Max 100 watt per socket) GU-24 Bi-pin Socket (Max 18 watt per socket)		Standard 120V
						LED: 16.8Watt 1600 Lumen	2700K 3500K 4000K	Standard 120V
BLE-C	*CGG*	*100*	*SBK*	*100*	*FST*	*LED*	*2700K*	

SAMPLE ORDER

ORDER SPECIFICS

BLE-								

Notes:

[1] Suitable for Damp location. Standard length 8 feet. Additional lengths available.

[2] Suitable for Dry location Only (Not CSA listed). Standard length 6 feet. Additional lengths available.

[3] Gooseneck and stems painted to match finish

[4] Clear glass not recommended for LED option.

Suitable for Wet Location (except when cord mounted)