



Item #	Diameter	Height
WHS12-PC	12"	7"
WHS14-PC	14"	7 ½"
WHS16-PC	16"	7 ¾"
WHS18-PC	18"	8 ½"
WHS20-PC	20"	9 ¼"

Model #	Item #	Standard Finishes	Mounting Options	Mounting Color	Optional Accessories	Accessory Colors	Wattage/Lamp Options	Ballast	Voltage
C- Cord Hung	WHS12-PC WHS14-PC WHS16-PC	<i>Other:</i> 975-Galvanized	<i>Cord:</i> Standard ¹ : SBK Black SWH White Cotton ² : CRZ Red Chevron CGM Grey CBK Black	<i>For Cord:</i> Canopy color: <i>Standards:</i> 975-Galv. for Galv. Shades 100-Black with Black Cord 200-White with White Cord <i>Custom with Twist Cord:</i> -CNY _____ ^Specify canopy color	CGG -Cast Guard and Glass ³	<i>Other:</i> 975-Galvanized	200 Watt maximum		
S- Stem Mount	WHS18-PC WHS20-PC	<i>Powder Coat:</i> 100-Black 200- White 300-Dark Green 600-Bronze 605-Rust	Cotton Twists ² : TBR Brown TBK Black TPT Putty TRD Red TWH White		WC -Wire Cage ⁴	<i>For additional colors, see color chart</i>			
G-Goose-Neck		<i>For additional colors, see color chart</i>	<i>Stem:</i> ST _____ ^Specify stem model	Powder Coat: 100-Black 200- White 300- Dark Green 600- Bronze 605- Rust	HSC -Hang Straight Canopy	<i>Vapor Proof Glass</i> ³ CLR - Clear FST - Frosted			
F- Flush Mount			<i>Gooseneck:</i> G _____ ^Specify gooseneck model		HDSM - Heavy Duty Stem Mount Canopy				
			<i>Flush Mount:</i> FM	<i>For additional mounting options and details, see mounting spec sheet</i>	HDBP - Heavy Duty Square Backing Plate				
BLE-F	WHS16-PC	200	FM	SAMPLE ORDER	CGG	FST SAMPLE ORDER			SAMPLE ORDER

ORDER SPECIFICS									
BLE-	-PC								

Notes:

¹ Suitable for Damp location. Standard length 8 feet. Additional lengths available.

² Suitable for Dry location Only. Standard length 6 feet. Additional lengths available. (Not CSA listed)

³ Guard/Glass option reduces wattage to 100 W

⁴ Not available for WHS20-PC.

Suitable for Wet Location (except when cord mounted)