




Job Name: _____
 Type: _____
 Quantity: _____

Item Number	Height (A)	Width (B)
H-15008	7"	8"
H-15010	8"	10"
H-15111	8"	11"
H-15112	8"	12"
H-15113	8"	13"
H-15114	9"	14"
H-15115	9"	15"

Item Number	Height (A)	Width (B)
H-15116	9 1/2"	16"
H-15117	10"	17"
H-15118	11"	18"
H-15120	11"	20"
H-15124	16"	24"
H-15127	18"	27"

Warehouse Shade Collection



Fixture No.	Fixture Color	Mounting	Mounting Color	Optional Accessories	Accessory Color	Wattage/Lamp options	Ballast	Voltage
H-15008 ⁽¹⁾	Standard ⁽²⁾	Mounting Options 1/2" 3/4" For H-15006, H-15008, H-15010 and H-15111 only. CB7 (7' Blk Cord) CW7 (7' Wht Cord) CG7 (7' Grey Mesh Cord) Cord Options ⁽³⁾ CB8 (8' Blk Cord) CW8 (8' Wht Cord) CG8 (8' Gray Mesh Cord) Custom Cord Options ⁽³⁾ CB (Black) CW (White) CG (Gray Mesh) Specify length. Stem Options (Stem 1/2") ST Specify length and canopy. HSC (Canopy) SMC (Canopy) Flush Mount Options FHSC FSMC Arm Options B-1 HL-K HL-A HL-U HL-H P-1 HL-C P-3 HL-D For all arms and specs see pages 321-344	Standard	CGU (Cast guard & glass) LCGU (Large cast guard & glass) WGU (Wire guard & glass) LWGU (Large wire guard & glass) ARN (Acorn globe) LARN (Large acorn globe) WGR (Wire guard) SK (Swivel knuckle) FX (Flexible tubing for cord mounted fixture only) For specs and glass color see pages 321-344.	Standard	Incandescent (Fixture is standard 100W or 200W. Do not specify.) CFL (4) (Compact Fluorescent) 13/CFL 18/CFL 26/32/42/CFL 26/CFL 32/CFL 42/CFL 57/CFL DMB (Dimmable Ballast for CFL. Add to Part No.) HID (4) (High Intensity Discharge) MH (4) (Metal Halide) 35/MH 50/MH 70/MH 100/MH 150/MH 175/MH HPS (4) (High Pressure Sodium) 50/HPS 70/HPS 100/HPS 150/HPS	Ballast option not available for INC. RB (5) (Remote) BCM (Canopy Mount) PLB (6) (Postline) For specs see pages 341-343.	Incandescent (Fixture is standard 120V. Do not specify.) CFL M (Multi 120/277V) HID RB and BCM M (Multi 120/208/240/277V) PLB 1 (120V) 2 (277V)
H-15010 ⁽¹⁾	93 (White)							
H-15111 ⁽¹⁾	95 (Dk. Grn)							
H-15112	96 (Galv.)							
H-15113 ⁽¹⁾	BR47 (Rust)							
H-15114	BK01, GN20.							
H-15115 ⁽¹⁾	Upgraded ⁽²⁾							
H-15116	Finishes							
H-15117	29, 66, 82, 90, 92, 94, 97, 99, 100, 103, 104, 105, 110, 112, 113, 114, 115, 117, 118, 119, 120, 127, 128, 129, 133, 134, 135, 136, 11, 98, 101, 102, 137, 121, 122, 123, 124, 125, 126, 01, 22, 25, 33, 77, 89, 24, 44, 48, 49, 15, 16, 55.							
H-15118	For finish specs see pages 344-348.							
H-15120								
H-15124								
H-15127								

H-15117 - 91 / 1/2" - 91 / CGU-CLR - 91 / 13/CFL - BCM - M

ORDER EXAMPLE

(USE THIS FORMAT TO PLACE ORDER)

Notes:

- H-15008, H-15010, H-15111 and H-15115 available for 100W Max INC. H-15008 and H-15010 not available with glass enclosures.
- For interior finish of fixture refer to color chart on pages 344-348. H-15124 and H-15127 not available in copper or brass finish.
- Cord Mounting wattage not to exceed 100 for HID. Gray Mesh Cord not available for HID.
- Requires Globe Option. (See pages 339-341 for Globe Options) Max Wattages for CGU and WGU are 100W INC, 32W CFL and 100W HID Max Wattages for LWGU, LCGU, ARN and LARN are 200W INC, 57W CFL and 175W HID.
- (RB) Remote Ballast not available for Fluorescent Lamping.
- (PLB) Post Line Ballast must specify 120V or 277V. (PLB) 50W MH requires a 3" dia. pole. (PLB) 70W and 100W MH require a 4" dia. pole. (PLB) 50W, 70W, 100W and 150W HPS require a 3" dia. pole.

Suitable for wet location.
 (Except when cord mounted)