




Job Name: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Quantity: \_\_\_\_\_

### Uplight Deep Bowl Shade Collection



Item Number	Height (A)	Width (B)
H-16312	13 1/2"	12"
H-16316	15"	16"
H-16318	16"	19"

Fixture No.	Fixture Color	Mounting	Mounting Color	Optional Accessories	Accessory Color	Wattage/Lamp options	Ballast	Voltage
<b>H-16312</b> <b>H-16316</b> <b>H-16318</b>	Standard <sup>(1)</sup> 91 (Black) 93 (White) 95 (Dk. Grn) 96 (Galv.) BR47 (Rust) BK01, GN20.  Upgraded Finishes 29, 66, 82, 90, 92, 94, 97, 99, 100, 103, 104, 105, 110, 112, 113, 114, 115, 117, 118, 119, 120, 127, 128, 129, 133, 134, 135, 136, 98, 101, 102, 137, 121, 122, 123, 124, 125, 126.  For finish specs see pages 344-348.	Mounting Options 1/2" 3/4"  Cord Options <sup>(2)</sup> CB8 (8' Blk Cord) CW8 (8' Wht Cord) CG8 (8' Gray Mesh Cord)  Custom Cord Options <sup>(2)</sup> CB__ (Black) CW__ (White) CG__ (Gray Mesh) Specify length.  Stem Options (Stem 1/2") __ST Specify length and canopy. HSC (Canopy) SMC (Canopy)  Flush Mount Options FHSC FSMC  Arm Options B-1 HL-K HL-A HL-U HL-H P-1 HL-C P-3 HL-D  For all arms and specs see pages 321-344.	Standard 91 (Black) 93 (White) 95 (Dk. Grn) 96 (Galv.) BR47 (Rust)  For all finishes see pages 344-348.	<b>SK</b> (Swivel knuckle)  <b>FX</b> (Flexible tubing for cord mounted fixture only)  For specs see pages 321-344.	Standard 91 (Black) 93 (White) 95 (Dk. Grn) 96 (Galv.) BR47 (Rust)  For all finishes see pages 344-348.	Incandescent (Fixture is standard 200W. Do not specify.)  CFL (Compact Fluorescent) 13/CFL 18/CFL 26/32/42/CFL 26/CFL 32/CFL 42/CFL 57/CFL  <b>DMB</b> (Dimmable Ballast for CFL. Add to Part No.)  HID (High Intensity Discharge)  MH (Metal Halide) 35/MH 50/MH 70/MH 100/MH 150/MH 175/MH  HPS (High Pressure Sodium) 50/HPS 70/HPS 100/HPS 150/HPS	Ballast option not available for INC.  <b>RB</b> <sup>(4)</sup> (Remote)  <b>BCM</b> (Canopy Mount)  <b>PLB</b> <sup>(5)</sup> (Postline)  For specs see pages 341-343.	Incandescent (Fixture is standard 120V. Do not specify.)  CFL <b>M</b> (Multi 120/277V)  HID RB and BCM <b>M</b> (Multi 120/208/240/277V)  PLB 1 (120V) 2 (277V)

H-16312 - 91 / 1/2" - 91 / SK - 91 / 13/CFL - BCM - M

**ORDER EXAMPLE**  
 (USE THIS FORMAT TO PLACE ORDER)

#### Notes:

- For interior finish of fixture refer to color chart on pages 344-348.
- Cord Mounting wattage not to exceed 100 for HID. Gray Mesh Cord not available for HID.
- Requires Globe Option (See pages 339-341 for Globe Options)  
 CGU and WGU Max Wattage 100W INC, 100W HID and 32W CFL.  
 LWGU, LCGU, ARN and LARN Max Wattage 200W INC, 175W HID and 57W CFL.
- (RB) Remote Ballast not available for Fluorescent Lamping.
- (PLB) Post Line Ballast must specify 120V or 277V.  
 (PLB) 50W MH requires a 3" dia. pole.  
 (PLB) 70W and 100W MH require a 4" dia. pole.  
 (PLB) 50W, 70W, 100W and 150W HPS require a 3" dia. pole.

Suitable for damp locations.  
 (Except when cord mounted)